

PRODUCT PROFILE

ALKASTRIP

TECHNICAL DATA

PRIMARY APPLICATION

AlkaStrip is an alkaline, non-ammoniated solution formulated to strip old polymer and wax coatings from vinyl, PVC and rubber floor coverings.

It is not advised to use AlkaStrip on linoleum floors.

The excellent blend of alkaline builders and solvents offer the following advantages:

- Quick penetration of polymer coating to reduce time and labour costs.
- Non-slip working conditions.
- Optimum surface wetting and solvent content to maximise pad life.
- Ammonia-free working environment.
- Simultaneous cleaning- and stripping action.

Soils removed by AlkaStrip: oil and light grease, scuff marks, wax- and polymer build-up.

APPLICATION PROCEDURE

Multi- & Difficult Coatings:

- Spread AlkaStrip undiluted over the floor area to be cleaned.
- Allow five (5) minutes contact time before mopping away old polymer dressing.
- Rinse well with clean water and allow the floor to dry before applying a new polymer coating.

Thin Coatings:

- Dilute AlkaStrip one (1) part concentrate on twenty (20) parts water. Spread the solution evenly over the floor area to be cleaned.
- Allow 5 – 10 minutes contact time before mopping away old floor dressing.

PRODUCT PROFILE

ALKASTRIP

TECHNICAL DATA

- Rinse well with clean water and allow floor to dry before applying a new polymer coating.

NB: Rinse the treated area well before applying the new polymer floor dressing with Hi Sol, Hi Shine, Floor Shine or Floor Bright).

Refer to the MSDS for the safety and handling precautions.

KEEP OUT OF REACH OF CHILDREN.